

new  
ker

<b>MODEL:</b> LAND 20MM			
<b>BRAND:</b> NEWKER	<b>CODE:</b> 187130	<b>COLOR:</b> CINDER	<b>DATE:</b> 06/26/2019
<b>CERAMIC TILES CLASSIFICATION (UNE-EN-14411): Grupo Bla. Anexo G</b>			

STANDARD	CHARACTERISTICS	TEST RESULT		
UNE-EN ISO 10545-4	Breaking strength	> 10 KN (1000 Kg)		
UNE-EN ISO 10545-4	Modulus of rupture	> 40 N/mm <sup>2</sup>		
UNE-EN ISO 10545-7	Resistance to surface abrasion			
	Class	3		
	Abrasion stage	-		
UNE-EN ISO 10545-11	Resistance to crazing	Resiste / Resist		
UNE-EN ISO 10545-12	Frost Resistance	Resiste / Resist		
UNE-EN ISO 10545-14	Resistance to staining			
	Fe <sub>2</sub> O <sub>3</sub> / Cr <sub>2</sub> O <sub>3</sub>	5		
	Iodine / alcohol solution	5		
	Light oil	5		
UNE-EN ISO 10545-13	Chemical Resistance			
	Household chemicals	Mín. Ga		
	Swimming pool salts	Mín. Ga		
	Citric Acid	Mín. Gla		
	Lactic Acid	Mín. Gla		
	Hydrochloric Acid low concentrations	Mín. GLA		
	Hydrochloric Acid high concentrations	Mín. GHA		
	Potassium Hydroxide low concentrations	Mín. GLA		
Potassium Hydroxide high concentrations	Mín. GHA			
<b>Dimension (mm)</b>	600,5x600,5		<b>Thickness (mm)</b>	20.0
<b>Slipperness</b>	C3 R12		<b>Water absorption</b>	E < 0,5%

new  
ker Nueva Cerámica NEWKER  
Costa de Azahar S.L.  
B-12880357 \* C/Grecia 63  
12006 - Castellón (Spain)