

new  
ker

<b>MODEL:</b> TEMPO			
<b>BRAND:</b> NEWKER	<b>CODE:</b> 205125	<b>COLOR:</b> GREY	<b>DATE:</b> 03/09/2021
<b>CERAMIC TILES CLASSIFICATION (UNE-EN-14411):</b> Grupo Bla. Anexo G			

STANDARD	CHARACTERISTICS	TEST RESULT		
UNE-EN ISO 10545-4	Breaking strength	Mín. 1300		
UNE-EN ISO 10545-4	Modulus of rupture	Mín. 35		
UNE-EN ISO 10545-7	Resistance to surface abrasion			
	Class	3		
	Abrasion stage	-		
UNE-EN ISO 10545-11	Resistance to crazing	Cumple / Passed		
UNE-EN ISO 10545-12	Frost Resistance	Resiste / Resist		
UNE-EN ISO 10545-14	Resistance to staining			
	Fe <sub>2</sub> O <sub>3</sub> / Cr <sub>2</sub> O <sub>3</sub>	Cumple / Passed		
	Iodine / alcohol solution	Cumple / Passed		
	Light oil	Cumple / Passed		
UNE-EN ISO 10545-13	Chemical Resistance			
	Household chemicals	Cumple /Passed		
	Swimming pool salts	Cumple / Passed		
	Citric Acid	Cumple/Passed		
	Lactic Acid	Cumple/Passed		
	Hydrochloric Acid low concentrations	Cumple/Passed		
	Hydrochloric Acid high concentrations	Cumple/Passed		
	Potassium Hydroxide low concentrations	Cumple/Passed		
Potassium Hydroxide high concentrations	Cumple/Passed			
<b>Dimension (mm)</b>	600,0x600,0		<b>Thickness (mm)</b>	9.0
<b>Slipperness</b>	C1		<b>Water absorption</b>	E < 0,5%

new  
ker

NUEVA CERÁMICA NEWKER CA SL  
B-12880357  
C/ Sta. Magdalena de Pulpis, 10  
12006 - CASTELLÓN (SPAIN)