

new  
ker

<b>MODEL:</b> TEMPO WALL			
<b>BRAND:</b> NEWKER	<b>CODE:</b> 205206	<b>COLOR:</b> GREY	<b>DATE:</b> 10/20/2020
<b>CERAMIC TILES CLASSIFICATION (UNE-EN-14411):</b> Grupo BIII. Anexo L			

STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-4	Breaking strength	Mín. 700
UNE-EN ISO 10545-4	Modulus of rupture	15
UNE-EN ISO 10545-7	Resistance to surface abrasion	
	Class	
	Abrasion stage	
UNE-EN ISO 10545-11	Resistance to crazing	Cumple / Passed
UNE-EN ISO 10545-12	Frost Resistance	
UNE-EN ISO 10545-14	Resistance to staining	
	Fe <sub>2</sub> O <sub>3</sub> / Cr <sub>2</sub> O <sub>3</sub>	5
	Iodine / alcohol solution	5
	Light oil	5
UNE-EN ISO 10545-13	Chemical Resistance	
	Household chemicals	Cumple /Passed
	Swimming pool salts	Cumple / Passed
	Citric Acid	Cumple/Passed
	Lactic Acid	Cumple/Passed
	Hydrochloric Acid low concentrations	Cumple/Passed
	Hydrochloric Acid high concentrations	Cumple/Passed
	Potassium Hydroxide low concentrations	Cumple/Passed
Potassium Hydroxide high concentrations	Cumple/Passed	
<b>Dimension (mm)</b>	250,0x750,0	
		<b>Thickness (mm)</b> 10.0
<b>Slipperness</b>		<b>Water absorption</b> E > 10%

new  
ker Nueva Cerámica NEWKER  
Costa de Azahar S.L.  
B-12880357 \* C/Gracia 63  
12006 - Castellón (Spain)