

new  
ker

<b>MODEL:</b> ETRA			
<b>BRAND:</b> NEWKER	<b>CODE:</b> 156109	<b>COLOR:</b> SAND	<b>DATE:</b> 06/26/2019
<b>CERAMIC TILES CLASSIFICATION (UNE-EN-14411):</b> Grupo Bla. Anexo G			

STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-4	Breaking strength	Mín. 1500
UNE-EN ISO 10545-4	Modulus of rupture	Mín. 35
UNE-EN ISO 10545-7	Resistance to surface abrasion	
	Class	-
	Abrasion stage	-
UNE-EN ISO 10545-11	Resistance to crazing	Cumple / Passed
UNE-EN ISO 10545-12	Frost Resistance	Resiste / Resist
UNE-EN ISO 10545-14	Resistance to staining	
	Fe <sub>2</sub> O <sub>3</sub> / Cr <sub>2</sub> O <sub>3</sub>	4
	Iodine / alcohol solution	4
	Light oil	4
UNE-EN ISO 10545-13	Chemical Resistance	
	Household chemicals	Mín. Gb
	Swimming pool salts	Mín. Gb
	Citric Acid	Mín. GLb
	Lactic Acid	Mín. GLb
	Hydrochloric Acid low concentrations	Mín. GLB
	Hydrochloric Acid high concentrations	Mín. GHB
	Potassium Hydroxide low concentrations	Mín. GLB
Potassium Hydroxide high concentrations	Mín. GHB	
<b>Dimension (mm)</b>	451,2x451,2	<b>Thickness (mm)</b> 9.3
<b>Slipperness</b>	C1	<b>Water absorption</b> E < 0,5%

new  
ker Nueva Cerámica NEWKER  
Costa de Azahar S.L.  
B-12880357 \* C/Grecia 63  
12006 - Castellón (Spain)